

The DCS CounterPoint Kiosk is a fully integrated countertop kiosk solution that unites the best kiosk features in compact, durable and aesthetically pleasing design. The Counter Point is Ready to Perform. Powered by an All In-One Windows PC the CounterPoint provides robust and responsive multimedia computing for a dynamic interactive experience as well as high uptime and availability of your critical kiosk applications. The CounterPoint is designed to withstand the demanding conditions of public installations and can be counted on for hassle-free and uninterrupted use.

The system may be manufactured in any color or texture and branded to give the system a unique appearance or match the décor of an installation site. A wide range of peripheral devices including barcode readers, RFID and EMV electronic payment devices, may be seamlessly and securely integrated with the CounterPoint, giving the system the ability to support even the most complex applications.



### 10 Pt Capacitive Touch Screen

Pivoting Monitor

Vandal Resistant Design

Weighted Base

Height Powered Windows PC

### Landscape Desktop Kiosk

Designed for Unattended Public Spaces

No Exposed Cables, Wires, or Ports

Commercial Grade LCD

19" (4:3) or 24" (16:9) Display Options

### Integrated Audio

Branding and Color Options

Ships Fully Assembled

Warranty Included

Integrated Peripheral Options



RETAIL



HEALTHCARE



ENTERTAINMENT  
& GAMING



GOVERNMENT  
& EDUCATION



HOSPITALITY

Digital Signage • Interactive Wayfinding/Directories • DOOH Advertising • Traffic Information



### KIOSK PC

Operating System	Windows 10
CPU	Intel i3, i5, or i7
RAM	8, 16, or 32GB DDR4
Storage	128GB SSD
Connectivity	Wifi, Ethernet, or 5G (AT&T) Touch System 10-Point PCAP
Input/Output	Ports HDMI x1 USB Port x2 Power Input AC 100-240V

### OPTIONAL PERIPHERALS

Biometric Device  
Payment Device  
Barcode Scanner  
RFID

SPECIFICATIONS	19"	24"
Max Resolution	1280x1024	1920x1080
Aspect Ratio	16:9	16:9
Brightness	300cd/m <sup>2</sup>	500cd/m <sup>2</sup>
Weight	15lbs	18lbs

**TEMPERATURE** 32°F to 120°F (Operational)

**CERTIFICATION** CE/FCC/RoHS

**WARRANTY** One Year On-Site Support; Extended Warranties Available